

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

L'Oreal USA Products, Inc.
111 Terminal Avenue
Clark, NJ 07066

L'Oreal Canada
4895 rue Hickmore
Ville St-Laurent, H4Y 1K5
Canada

Emergency Telephone Number:
1-800-535-5053 (International: 352-323-3500)
In Canada – 1-613-996-6666 (Canutec) (*666 cellular)

For further information:
1-732-499-2741

Poison Control Number: 412-390-3326




Product Name: Logics Luminous Cream Lightener
L'Oreal Professionnel Platinum Lightening Paste
Redken Blonde Icing Cream Lightener
Redken Blonde Glam Cream Lightener


Recommendations on use: Personal care product to be mixed with companion product(s) in accordance with instructions and applied to hair for lightening effect.

Restrictions on use: For external use only. Use only as directed.

SECTION 2: HAZARDS IDENTIFICATION

Signal Word: DANGER

Symbol	Classification	Hazard Statement	Prevention Statements
	Self-Heating Category 2	Self-heating in large quantities May catch fire	<ul style="list-style-type: none"> Keep cool. Protect from sunlight.
	Eye Damage Category 1	Causes serious eye damage	<ul style="list-style-type: none"> Wash hands and all skin surfaces contacted thoroughly after handling Wear nitrile or vinyl gloves. Wear eye protection appropriate for the manufacturing operation being performed (goggles or face shield).
	Sensitization Respiratory	May cause allergy or asthma symptoms or breathing difficulties if inhaled	<ul style="list-style-type: none"> Avoid breathing dust. In case of inadequate ventilation wear respiratory protection

Symbol	Classification	Hazard Statement	Prevention Statements
	Acute Toxicity Oral Category 4	Harmful if swallowed	<ul style="list-style-type: none"> Do not eat, drink or smoke when using this product
No symbol Required	Sensitization – Skin Category 1	May cause an allergic skin reaction	<ul style="list-style-type: none"> Contaminated work clothing must not be allowed out of the workplace
No symbol Required	Skin Irritation Category 2	Causes skin irritation	<ul style="list-style-type: none"> See prevention statements above
No symbol Required	Specific Target Organ Toxicity (Single Exposure) Category 3	May cause respiratory irritation	<ul style="list-style-type: none"> Use only outdoors or in a well-ventilated area

This material is considered hazardous by the US Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200)

General Precautionary Statements: Keep out of reach of children. Read label/directions before use. Keep from heat and moisture. Do not use metal utensils.

Hazards Not Otherwise Classified: None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Only hazardous constituents associated with the product are listed below

<u>INGREDIENT:</u>	<u>CAS NO.</u>	<u>% WT</u>
EDTA	60-00-4	≤ 0.8%
Titanium Dioxide	13463-67-7	≤ 1.0%
Sodium Lauryl Sulfate	68585-47-7	≤ 4.0%
Sodium Metasilicate	6834-92-0	≤ 5.5%
Ammonium Persulfate	7727-54-0	≤ 15.0%
Sodium Silicate	1344-09-8	≤ 15.0%
Potassium Persulfate	7727-21-1	≤ 30.0%

SECTION 4: FIRST AID MEASURES

Response Statements:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing until material is sufficiently removed from the eye. **If eye irritation persists:** Immediately call a poison control center or get medical advice/attention.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. **If skin irritation or rash occurs:** Get medical advice/attention.

IF INHALED: If breathing is difficult, remove person to fresh air and keep in a position comfortable for breathing. **If experiencing respiratory symptoms:** Call a poison control center or get medical advice/attention.

IF SWALLOWED: Rinse mouth. Do not induce vomiting. Never give anything by mouth to an unconscious individual. Call a poison control center or get medical advice/attention if you fell unwell.

SYMPTOMS/EFFECTS: Causes serious eye damage. May cause asthma symptoms or breathing difficulties. Harmful if swallowed. May cause an allergic skin reaction. Causes skin irritation. May cause respiratory irritation.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Consult product labeling. No special advice.

SECTION 5: FIRE-FIGHTING MEASURES

Notes for Non-Emergency Personnel:

EXTINGUISHING MEDIA: In case of fire: Use carbon dioxide, dry chemical and/or foam to extinguish. Water spray may be used to soak other materials surrounding the product, to prevent the spread of the fire. Selection of a fire extinguisher should also be appropriate to address the location of the fire and equipment involved. Review the tools available at your location to ensure proper availability of equipment.

Notes for those trained to participate in an emergency:

SPECIAL FIRE FIGHTING PROCEDURES: Follow National Fire Protection Association Guidelines or local guidelines appropriate for emergency response.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Persulfates yield oxygen and may stimulate combustion of flammable and combustible materials.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal degradation may produce oxygen, ammonia, oxides of carbon, sulfur, hydrocarbons, and/or derivatives.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Notes for non-emergency personnel:

Consult trained response personnel for clean-up of large spills or locations where providing preliminary control of the chemical release is hazardous. Hazardous locations include areas where ignition sources cannot be controlled and where mixture with organic material is possible. Isolate the area and deny entry to unnecessary and unprotected personnel. Sections 2, 5, 7 and 8 of this document should be consulted upon use of material, to become knowledgeable of the material's hazards and how to control associated risks.

If the location is not hazardous and only a small amount of material is released, the material can be swept up or wiped with damp towels/sponges while wearing the protective equipment as noted below. Clean the area with detergent and water. Prohibit discharge to drains, soil, surface and ground waters. Dispose in accordance with section 13 of this document.

PERSONAL PROTECTIVE EQUIPMENT: Nitrile or vinyl gloves, safety glasses/goggles and protective clothing (e.g. apron) may be required for clean-up of large releases. Respiratory protection is typically not necessary, but may be used depending upon the size of the spill and occupational exposure limits. Respiratory protection may include the use of particulate cartridges. See also section 8 of this document.

Notes for those trained to participate in an emergency:

ACCIDENTAL RELEASE MEASURES: Materials in powder form are not expected to migrate greatly during release. Released material should be swept up and accumulated in appropriate UN specification containers while minimizing dust generation. Wash area completely with water. Take care to avoid contact with wet surfaces or walkways that may become slick when residue is present. Rinse response equipment (e.g. towels, sponges, mops) thoroughly prior to disposal or storage. Prohibit discharge to drains, soil, surface and ground waters.

Recommendations for personal protective equipment selection are noted above. Dispose in accordance with section 13 of this document.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Do not eat, drink or smoke while working with hazardous chemicals. Employees should be advised to wear appropriate protective equipment in the manufacturing environment. See section 8 of this document for protective equipment selection. Use only with adequate ventilation and avoid inhalation. Avoid contact with eyes and skin. Do not use with metal utensils. All manufacturing should be performed indoors, in an enclosed environment.

Maintain a clean work environment which includes use of properly functioning containers, proper housekeeping practices.

CONDITIONS FOR SAFE STORAGE:

Storage precautions for unpackaged product (manufacturing environment): Keep in a cool and well-ventilated area. Keep containers closed when not in use. Store away from moisture. Do not store metal utensils with product. Maintain air gap between stacks/pallets. Store bulk masses greater than 450L at temperatures not exceeding 50°C/122°F. Store away from other materials. Store in a location where spill containment will be easily accessible and releases can be contained.

Storage precautions for packaged product: See consumer packaging.

Keep away from open drains and access to the environment.

Incompatible materials: Organic compounds and reducing agents. Store away from incompatible materials and moisture.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS: These criteria have been published by the referenced authority to establish exposure limits in the work environment. Employee work areas should be monitored to ensure that permissible limits are not exceeded during the work day. These references do not coincide with product use. These references are meant to be in association with the manufacturing environment.

OCCUPATIONAL EXPOSURE VALUES:

Component Name (CAS-No.)	Reference	TWA		STEL/CEILING	
		ppm	mg/m ³	ppm	mg/m ³
Titanium Dioxide (13463-67-7)	OSHA PEL	--	15°	--	--
	ACGIH TLV	--	10	--	--
	NIOSH REL	--	--	--	--
Ammonium Persulfate (as S ₂ O ₈) 7727-54-0	OSHA PEL	--	--	--	--
	ACGIH TLV	--	0.1	--	--
	NIOSH REL	--	--	--	--

Potassium Persulfate (Persulfates) 7727-21-1	OSHA PEL	--	--	--	--
	ACGIH TLV	--	0.1	--	--
	NIOSH REL	--	--	--	--

Notes: ° (OSHA) – Total Dust

No occupational exposure values have been published for other constituents noted in Section 3.

WORK HYGIENIC PRACTICES: Ensure all work surfaces are maintained, to prevent contamination.

ENGINEERING CONTROLS: None required for product use. For handling large quantities of material, such as in the manufacturing of product, ventilation should be utilized. This ventilation should be compatible with the control of oxidizing materials. Exhaust ventilation should be utilized to maintain air concentrations of material below the occupational exposure guidelines noted above.

Local exhaust ventilation is not typically required for product use. For handling large quantities of material, such as in the manufacturing of product -- Local Exhaust: Explosion proof. Mechanical (general): Explosion proof.

PERSONAL PROTECTIVE EQUIPMENT: Consistent with good hygiene practices, personal protective equipment (PPE) should be used in conjunction with other control measures including engineering controls, ventilation and isolation. See also Section 5 of this document for PPE advice, in the event of an emergency.

Eye/Face Protection (Non-Emergency): None required for product use. Contact with eyes should be avoided. For handling of large quantities of material, safety glasses with side shields/goggles are recommended.

Skin Protection (Non-Emergency): Gloves should be worn when mixing kit components and applying mixture. For handling large quantities of material, such as in product manufacturing, nitrile or vinyl gloves should be considered for use. Tyvek clothing may also be suitable for handling large quantities of material in the manufacturing environment.

Respiratory Protection (Non-Emergency): Respiratory protection is not required for product use. For manufacturing of product, respiratory protection such may be considered. Ensure that the respirator meets current local occupational health and safety standards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Bluish paste
ODOR:	Not Available
ODOR THRESHOLD:	Not Available
pH:	10.1 – 10.5 (Solution)
MELTING/FREEZING POINT:	F: Not Available C: Not Available
BOILING POINT:	F: Not Available C: Not Available
FLASH POINT:	F: > Not Applicable C: >Not Applicable METHOD USED: Not Applicable
EVAPORATION RATE:	Not Applicable
FLAMMABILITY:	Not Applicable
VAPOR PRESSURE (mmHg):	@ 70F: Not Available @ 21 C: Not Available
VAPOR DENSITY (AIR = 1):	@ 70F: Not Available @ 21 C: Not Available

RELATIVE DENSITY (H₂O = 1): Not Available

SOLUBILITY IN WATER: Not Available

PARTITION COEFFICIENT: Not Available

AUTOIGNITION TEMPERATURE: Not Available

DECOMPOSITION TEMPERATURE: Not Available

VISCOSITY: Not Available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Material is not considered reactive under typical handling and storage conditions. Heat and/or moisture may cause instability.

STABILITY: Product is stable.

POSSIBILITY OF HAZARDOUS REACTIONS: None known. Hazardous polymerization is not expected to occur.

CONDITIONS TO AVOID: Heat, moisture and contamination with organic materials and metal utensils.

INCOMPATIBILITY (MATERIAL TO AVOID): Organic compounds and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal degradation may produce oxygen, ammonia, oxides of carbon, sulfur, hydrocarbons, and/or derivatives.

SECTION 11: TOXICOLOGICAL INFORMATION

Where information is not listed specifically for constituents, published information was not available.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS:

SKIN CORROSION/IRRITATION: Causes skin irritation

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye damage

RESPIRATORY/SKIN SENSITIZATION: May cause allergic reaction/breathing difficulty; May cause allergic skin reaction

INGESTION: Harmful if swallowed.

INHALATION: May cause respiratory irritation

ROUTES OF EXPOSURE: Eyes, skin, ingestion, inhalation

SYMPTOMS: Causes serious eye damage. May cause asthma symptoms or breathing difficulties. Harmful if swallowed. May cause an allergic skin reaction. Causes skin irritation. May cause respiratory irritation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Existing dermatological conditions (such as eczema) and respiratory conditions (such as bronchial asthma and/or bronchitis) may be exacerbated.

ACUTE TOXICOLOGY DATA FOR COMPONENTS

Material	Route	Species	Test Results
EDTA	Oral LD ₅₀	Rat (OECD 401 eq.)	4,500 mg/kg bw
EDTA	Inh. LC ₅₀ (6h)	Rat (Dust)	>1 mg/l air
Titanium Dioxide	Oral LD ₅₀	Rat	>5,000 mg/kg bw
Sodium Lauryl Sulfate	Oral LD ₅₀	Rat	6,000 mg/kg bw
Sodium Lauryl Sulfate	Dermal LD ₅₀	Rabbit	600 mg/kg bw
Sodium Lauryl Sulfate	LC ₅₀ (4 hr)	Rat	8.67 mg/l air
Sodium Metasilicate	Oral LD ₅₀	Rat	1,152 mg/kg bw
Ammonium Persulfate	Oral LD ₅₀	Rat (OECD 401)	700 mg/kg bw
Ammonium Persulfate	Dermal LD ₅₀	Rat (OECD 402)	>2,000 mg/kg bw
Ammonium Persulfate	LC ₅₀ (4 hr)	Rat (EPA OPP 81-3)	>2.95 mg/l air
Sodium Silicate	Oral LD ₅₀	Rat (OECD 401 eq.)	3,400 mg/kg bw
Sodium Silicate	Dermal LD ₅₀	Rat	>5,000 mg/kg bw
Potassium Persulfate	Oral LD ₅₀	Rat (OECD 401 eq.)	1,130 mg/kg bw
Potassium Persulfate	Dermal LD ₅₀	Rabbit	>10,000 mg/kg bw
Potassium Persulfate	LC ₅₀ (1 hr)	Rat	>42.9 mg/l air

Skin Corrosion/Irritation:

<i>EDTA:</i>	Not Irritating (Rabbit)
<i>Titanium Dioxide:</i>	Not Irritating (Rabbit)
<i>Sodium Lauryl Sulfate:</i>	Slightly/ Moderately Irritating: 0.5% - 10%; Skin Corrosion: 10% - 30% (Rat)
<i>Sodium Metasilicate:</i>	Corrosive (Rabbit, OECD 404)
<i>Ammonium Persulfate:</i>	Not Irritating (Rabbit, OECD 404)
<i>Sodium Silicate:</i>	Corrosive (≥ 28%); Irritating (<28%) (Rabbit, 16 CFR 1500.42)
<i>Potassium Persulfate:</i>	Irritating (Rabbit)

Serious Eye Damage/Irritation:

<i>EDTA:</i>	Irritating (Rabbit)
<i>Titanium Dioxide:</i>	Not Irritating (Rabbit)
<i>Sodium Lauryl Sulfate:</i>	Mildly Irritating: 5.1%; Moderately Irritating: 10%; Severely Irritating: 21% (Rat)
<i>Sodium Metasilicate:</i>	Corrosive (In Vitro, IRE)
<i>Ammonium Persulfate:</i>	Slightly Irritating (Rabbit, OECD 405)
<i>Sodium Silicate:</i>	Corrosive (≥ 39%); Irritating (<39%) (Rabbit, OECD 404)
<i>Potassium Persulfate:</i>	Irritating (Rabbit)

Respiratory Irritation:

<i>Sodium Metasilicate:</i>	Irritating
<i>Ammonium Persulfate:</i>	Irritating (Human)
<i>Sodium Silicate:</i>	Irritating
<i>Potassium Persulfate:</i>	Irritating (Human)

Skin Sensitization:

<i>EDTA:</i>	Not Sensitizing (Guinea Pig, OECD 406)
<i>Sodium Lauryl Sulfate:</i>	Possibly sensitizing with repeated contact
<i>Sodium Metasilicate:</i>	Not Sensitizing (Guinea Pig, OECD 429)
<i>Ammonium Persulfate:</i>	Sensitizing (Guinea Pig, OECD 406)
<i>Sodium Silicate:</i>	Not Sensitizing (Human, RIPT)
<i>Potassium Persulfate:</i>	Sensitizing (Mouse, OECD 429 eq.)

CHRONIC HEALTH HAZARDS:

REPEAT DOSE TOXICITY:

NOAEL (*Titanium Dioxide*, oral): 24,000 mg/kg (Rat)
 NOAEL (*Sodium Lauryl Sulfate*, oral): 100 mg/kg/day (Rat)
 NOAEL (*Sodium Metasilicate*, oral): >227 mg/kg bw/day (Rat, 90d)
 NOAEL (*Ammonium Persulfate*, oral): 41.1 mg/kg bw/day (Rat, OECD 407 eq., 28d)
 NOAEC (*Ammonium Persulfate*, inh.): 10.3 mg/m³ air (Rat, OECD 413, 90d)
 NOAEL (*Sodium Silicate*, oral): 2,400 mg/kg bw/day (Rat, OECD 407 eq., 90d)
 NOAEL (*Potassium Persulfate*, oral): 131.5 mg/kg bw/day (Rat, OECD 407 eq., 28d)

CARCINOGENICITY:

Component Name (CAS-No.)	OSHA	ACGIH	NTP	IARC
Titanium Dioxide (13463-67-7)	--	TLV-A4	--	IARC-2B

ACGIH TLV-A4 – This reference indicates that the material is “Not Classifiable as a Human Carcinogen”.
 IARC-2B – This reference indicates that the material is “Possibly Carcinogenic to Humans”

These products contain titanium dioxide which has received its carcinogenic classification based on exposure in the respirable form. These materials in this product are not in their respirable form and are intended for application to hair.

MUTAGENICITY:

EDTA: A variety of *in vitro* and *in vivo* tests have products negative results.
Titanium Dioxide: A variety of *in vitro* tests have produced negative results.
Sodium Lauryl Sulfate: A variety of *in vitro* and *in vivo* tests have products negative results.
Sodium Metasilicate: A variety of *in vitro* and *in vivo* tests have products negative results.
Ammonium Persulfate: A variety of *in vitro* tests have produced negative results.
Sodium Silicate: A variety of *in vitro* and *in vivo* tests have products negative results.
Potassium Persulfate: A variety of *in vitro* tests have produced negative results.

REPRODUCTIVE TOXICITY:

Sodium Lauryl Sulfate: No adverse effect was seen on fertility.
Ammonium Persulfate: NOAEL: ≥ 250 mg/kg bw/d (Rat, OECD 421)
Sodium Silicate: NOAEL: >159 mg/kg bw/d (Rat) – No reproductive effects

DEVELOPMENTAL TOXICITY/TERATOGENICITY:

EDTA: NOAEL: ≥ 967 mg/kg bw/d (Rat) – No developmental effects
Sodium Lauryl Sulfate: NOAEL: 300 mg/kg/day; LOAEL: 600 mg/kg/day (Mice/Rat)
Sodium Metasilicate: NOAEL: > 200 mg/kg bw/day (Mouse)
Ammonium Persulfate: NOAEL: ≥ 250 mg/kg bw/d (Rat, OECD 421)

SECTION 12: ECOLOGICAL INFORMATION

Contact with the environment should be avoided. Spills and leaks should be immediately cleaned up and removed. All precautions should be taken to prevent contact with the environment. Published information regarding ingredients listed on this document area found below; where data is not listed, documentation was unavailable.

ACUTE AND PROLONGED TOXICITY TO FISH

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
EDTA	LC ₅₀	159 mg/L	Lepomis macrochirus	96 h
Titanium Dioxide	LC ₅₀	>1,000 mg/L	Leuciscusidus idus	48 h
Sodium Metasilicate	LC ₅₀ (ISO 7346)	210 mg/L	Danio rerio	96 h
Ammonium Persulfate	LC ₅₀ (EPA OPP 72-1)	76 mg/L	Oncorhynchus mykiss	96 h
Sodium Silicate	LC ₅₀ (OECD 203)	1,108 mg/L	Danio rerio	96 h
Potassium Persulfate	LC ₅₀	76 mg/L	Oncorhynchus mykiss	96 h

ACUTE TOXICITY TO AQUATIC INVERTEBRATES

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
EDTA	EC ₅₀ (DIN 38412, 11)	625 mg/L	Daphnia Magna	25 h
Sodium Lauryl Sulfate	EC ₅₀	5.55 mg/L	Ceriodaphnia Dubia	48 h
Ammonium Persulfate	EC ₅₀ (EPA OPP 72-2)	120 mg/L	Daphnia Magna	48 h
Sodium Silicate	EC ₅₀ (EU Method C.2)	1,700 mg/L	Daphnia Magna	48 h
Potassium Persulfate	EC ₅₀	120 mg/L	Daphnia Magna	48 h

TOXICITY TO AQUATIC PLANTS

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
Titanium Dioxide	EC ₅₀	61 mg/L	Pseudokirchneriella subcapitata	72 h
Sodium Lauryl Sulfate	EC ₅₀	> 120mg/L	Green Algae	72 h
Ammonium Persulfate	EC ₅₀ (OECD 201)	83.7 mg/L	Pseudokirchneriella subcapitata	72 h
Sodium Silicate	EC ₅₀ (DIN 38412, 9)	>345.4 mg/L	Desmodesmus subspicatus	72 h

TOXICITY TO MICROORGANISMS

INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
EDTA	EC ₅₀	2.4 mmol/L	Microorganism	24 h
Titanium Dioxide	EC ₅₀	5-30 mg/L	Activated Sludge	3 h
Sodium Lauryl Sulfate	EC ₅₀	0.38 mg/L	Photobacterium Phosphoreum	15 min
Sodium Metasilicate	EC ₅₀ (OECD 209)	> 100 mg/L	Activated Sludge	3 h
Ammonium Persulfate	EC ₁₀ (NEN 6509)	36 mg/L	Pseudomonas putida	18 h
Sodium Silicate	EC ₀ (DIN 38412, 27)	3,454 mg/L	Pseudomonas putida	30 min

PERSISTENCY AND DEGRADABILITY:

EDTA: 37% (14d) – OECD 302 B – Inherently Biodegradable

BIOACCUMULATIVE POTENTIAL:

EDTA: BCF: 1.1; log Pow: -3.86 (Est.) – Not expected to bioaccumulate

Sodium Metasilicate: Not expected to bioaccumulate

Ammonium Persulfate: Not expected to bioaccumulate

Sodium Silicate: Not expected to bioaccumulate

Potassium Persulfate: Not expected to bioaccumulate

SECTION 13: DISPOSAL CONSIDERATIONS

Those responsible for the performance of disposal, recycling or reclamation activities should refer to Section 8 of this document for advice on personal protective equipment and exposure controls.

WASTE DISPOSAL CONTAINERS: Appropriate US DOT containers should be utilized which may include cardboard boxes for products, plastic/lined drums for solids. These containers should meet the packaging specifications required for DOT compliance. Packaging containers must not include incompatible materials.

WASTE DISPOSAL METHOD: As manufactured, this product exhibits the ignitable (D001) RCRA characteristic of hazardous waste. Controlled incineration at a licensed waste facility is the recommended technology for treatment and disposal. Material must not be disposed of through sewage.

RCRA HAZARD CLASS: D001

Follow all local governmental requirements intended for disposal.

SECTION 14: TRANSPORT INFORMATION

North American Ground Transportation

- **IN CONSUMER PACKAGING:**

UN ID Number: UN 3088
Proper Shipping Name: Self-heating, solid, organic, n.o.s
Technical Name: Potassium persulfate, ammonium persulfate
Hazard Class: 4.2
Packing Group: II
Label Statements: Spontaneously Combustible (Division 4.2)

- **OTHER THAN CONSUMER PACKAGING:**

UN ID Number: UN 3088
Proper Shipping Name: Self-heating, solid, organic, n.o.s
Technical Name: Potassium persulfate, ammonium persulfate
Hazard Class: 4.2
Packing Group: II
Label Statements: Spontaneously Combustible (Division 4.2)

Transport Via Water

- **IN CONSUMER PACKAGING:**

UN ID Number: UN 3088
Proper Shipping Name: Self-heating, solid, organic, n.o.s
Technical Name: Potassium persulfate, ammonium persulfate
Hazard Class: 4.2
Packing Group: II
Label Statements: Spontaneously Combustible (Division 4.2)

- **OTHER THAN CONSUMER PACKAGING:**

UN ID Number: UN 3088
Proper Shipping Name: Self-heating, solid, organic, n.o.s
Technical Name: Potassium persulfate, ammonium persulfate
Hazard Class: 4.2
Packing Group: II
Label Statements: Spontaneously Combustible (Division 4.2)

Transport Via Air (Domestic/International)

- **IN CONSUMER PACKAGING:**

UN ID Number: UN 3088
Proper Shipping Name: Self-heating, solid, organic, n.o.s
Technical Name: Potassium persulfate, ammonium persulfate
Hazard Class: 4.2
Packing Group: II
Label Statements: Spontaneously Combustible (Division 4.2)

- **OTHER THAN CONSUMER PACKAGING:**

UN ID Number: UN 3088
Proper Shipping Name: Self-heating, solid, organic, n.o.s
Technical Name: Potassium persulfate, ammonium persulfate
Hazard Class: 4.2
Packing Group: II
Label Statements: Spontaneously Combustible (Division 4.2)

Please be aware of carrier transport variations before shipping hazardous materials.

SECTION 15: REGULATORY INFORMATION

National Fire Protection Association Codes: Health: 2 Fire: 0 Reactivity: 1 Other: OX

Workplace Hazardous Materials Identification System: Class D; Division 2, Subdivision B; Corneal Damage/Skin Irritation;

This regulatory information represents the product, in its consumer packaging.

SECTION 16: OTHER INFORMATION

PREPARATION INFORMATION: This document replaces the version dated July 28, 2011 and all previous versions of safety data sheet related to this product.

Author: Ronald Weslosky (Corporate Regulatory Services)